ACUDOR ACCESS PANELS

YOUR AUTHORIZED ACUDOR DISTRIBUTOR

APPLICATION

Designed for interior and exterior applications that require an access opening that will blend in with the surrounding floor material

FEATURES

• Recessed 1" to accommodate ceramic tile/concrete

• To keep the floor material from cracking or chipping within the door panel, the security screws are located in the flange of the mounting frame

SPECIFICATIONS

MATERIAL: Aluminum

DOOR: 1/4" smooth aluminum plate reinforced for live loads of 150 pounds/sq.ft. / recessed 1" for ceramic tile/concrete

FRAME: 1-1/2" x 1-1/4" aluminum angle with mounting holes in top flange

STANDARD LATCH: Door panel is secured to frame with 1/4" x 1" flat head screws

FINISH: Mill finish



For a complete list of options visit www.AcudorAccessPanels.com



To view Pricing and Additional Product Info.


SKU: FT-8080-1 FLOOR DOOR NON HINGED **PANEL RECESSED 1**" FOR CERAMIC TILE/CONCRETE





DIMENSIONS AND APPEARANCE


>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES: DOOR SIZE W x H WEIGHT INCHES (MM) LBS KG 8 x 8 (203 x 203) 2.7 6 9 4.1 12 x 12 (305 x 305) 18 x 18 (457 x 457) 18 8.2 24 x 24 (610 x 610) 36 16.3









NOTES: MATERIAL: ALUMINUM · LOADING: 150 LBS. PER SQ. FT.

• 316 STAINLESS STEEL NUTS & BOLTS

Proprietary property of Acudor Products, Inc., sold and distributed with proper authorization

PROJECT DATA **Custom Sizes Available - Fast!** PROJECT NAME : QTY w OPTIONS Н ARCHITECT : DEALER CONTRACTOR LOCATION SPECIAL INSTRUCTIONS DATE SUBMITTAL APPROVAL TAGGING INSTRUCTIONS : (signature or stamp)





NEW YORK 10163-4668



WEBSITE: www.AcudorAccessPanels.com

E-MAIL: info@AcudorAccessPanels.com

SUBMITTAL/TECHNICAL DATA SHEET



PO BOX 4668 PMB 76520 NEW YORK, NEW YORK 10163-4668 US

FT-8080-1

NON-HINGED PANEL RECESSED 1" For ceramic tile/concrete

NOMINAL DOOR SIZE	FRAME OPENING		RECEIVING AREA		OVERALL SIZE		WEIGHT
in. (mm)	A in. (mm)	B in. (mm)	C in. (mm)	D in. (mm)	E in. (mm)	F in. (mm)	LBS. (KG)
8 x 8	8.750 (222)	7.750 (222)	8.125 (206)	8.125 (206)	11.750 (298)	11.750 (298)	5 (2.2)
12 x 12	12.750 (324)	11.750 (324)	12.125 (308)	12.125 (308)	15.750 (476)	15.750 (476)	7 (3.2)
18 x 18	18.750 (476)	17.750 (476)	18.125 (460)	18.125 (460)	21.750 (552)	21.750 (552)	15 (6.8)
24 x 24	24.750 (629)	23.750 (629)	24.125 (613)	24.125 (613)	27.750 (705)	27.750 (705)	36 (16.3)

